Ultra**Heat S** Series

FEATURES

- Output regulation Voltage, Power, Current
- Limits Current, DC Volts, Output Volts, Power, Frequency
- Compact air cooled power supply design with automatic fan control
- Operator controls Selectable Advanced, or Basic control panels
- Capable of delivering full power in the 50-250kHz frequency range
- Variable ratio output isolation transformer for load matching of a wide range of loads and coils



- Notional RS232/485 interface for remote computer monitoring, control and diagnostics
- Now Power control from 1 to 120% in 1% increments (50%/10sec max duty cycle operation above 100%)
- Multiple timer controls with up to 5 ramp/soak steps
- 0-10V or 4-20mA external control and remote Start/Stop operation



SPECIFICATIONS

Model	Output kW	Pulsed kW	Frequency kHz	AC Line Volts (1phase)	Line Freq. Hz	Power Lb Supply (kg) Weight	Power Supply inch (cm) WxDxH	Heat Lb Station (kg) Weight	Heat Station inch (cm) WxDxH	Water GpM (LpM)
UPT-S 1.5/250-E	1.5	1.8	50-250	110/230	50/60	13.2 (6)	7"x9.5"x12.4" (18x24x31.5)	15.4 (7)	7"x9.5"x8.3" (18x24x21)	0.5 (2)
UPT-S 2/250	1.2	1.5		110						
	2	2		230					(10/24/21)	(2)
UPT-S 4/250	3	3.6		230		44	14"x14"x11.2"	46.3	14"x14"x8.7"	1
	4	5			(20)	(36x36x28.5)	(21)	(36x36x22)	(4)	

BENEFITS

- Advanced, cost effective power supplies utilizing the latest switching power supply technology
- Adaptive digital phase control providing very efficient operation in a wide frequency range
- ☑ Reliable, modular system, easy to maintain and service
- Solution States St
- Configured to operate with external Heat Stations allowing output connections to be available from all sides
- Easy remote operation both via Heat Station and Remote Control Panel
- Durable design, loaded with safety and diagnostics features
- Serial or Wireless Communication link to a PC based software (optional)

OPTIONAL EQUIPMENT

■ Remote Control Panel

■ Compact water cooling unit



2360 Hamburg Turnpike Wayne,

NJ 07470

TEL: (973)-248-3366 FAX: (973)-248-3366